



SCOTT STEREO AMPLIFIER A 437

INPUT
tuner
MIC AUX
phone

SELECTOR

mono stereo rev
L R L R
L R

MODE

right

TONE CONTROL

+12dB

BASS TREBLE

-12dB

left right

left right

POWER LEVEL

low high

FILTER

ON

LOUD off

norm 1 source

2 monitor


TAPE

A

SPEAKERS

PHONES

POWER

 **SCOTT** STEREO AMPLIFIER A 437



left right
└────────── POWER LEVEL ─────────┘



max
VOLUME




right
BALANCE



FILTER

low

high



LOUD

off



TAPE

norm

1

source



SPEAKERS



PHONES



POWER



CAUTION: PLEASE DISCONNECT LINE CORD BEFORE REPLACING FUSE.

AVIS: S.V.P. DEBRANCHER LE FIL DU POUVOIR AVANT DE REMPLACER LE FUSIBLE.
1.75A, 5L0-BLO 250V.

SCOTT
STEREO AMPLIFIER
MODEL NO. A437

H. H. SCOTT INC.
20 COMMERCE WAY
WOBURN, MA 01801
U.S.A.

CAUTION: TO PREVENT ELECTRIC SHOCK DO NOT REMOVE SCREWS.
ATTENTION: AFIN D'EVITER DES CHOCS ELECTRIQUES, N'ENLEVEZ PAS LES VIS.

SPEAKER CAUTION: USE 8 OHM MIN. SPEAKERS.
ATTENTION: UTILIZER DES HAUT-PARLEURS 8 OHM MIN.

SWITCHED

UNSWITCHED

OUTLET RATING:
SPECIFICATION DU RECEPTACLE:
230V, 50/60Hz
SWITCHED: CONTRÔLE: 50W, MAX.
UNSWITCHED: NONCONTRÔLE:
150W, MAX.

NONCONTRÔLE

POWER FUSE
CONTRÔLE

ELECTRICAL RATING
SPECIFICATIONS ELECTRIQUES:

A.C.
INPUT
W/ACC. 50W

R. CHANNEL

3.5A F.B.

R G G L

SPEAKER B

R G G L

SPEAKER A

L. CHANNEL

3.5A F.B.

M.A. INP. A. OUT - AUX - TUNER - 2 PHONO

LEFT

RIGHT

OUT-2-IN - OUT-1-IN - REC./PB

LEFT

RIGHT

TAPE RECORDER

ON

CAUTION: PLEASE DISCONNECT LINE CORD BEFORE REPLACING FUSE.

AVIS: S.V.P. DEBRANCHER LE FIL DU POUVOIR AVANT DE REMPLACER LE FUSIBLE.
1.75A, 5LO-BLO 250V.

SCOTT
STEREO AMPLIFIER
MODEL NO. A437

H. H. SCOTT INC.
20 COMMERCE WAY
WOBURN, MA 01801
U. S. A.

CAUTION: TO PREVENT ELECTRIC SHOCK DO NOT REMOVE SCREWS.
ATTENTION: AFIN D'EVITER DES CHOCS ELECTRIQUES. N'ENLEVEZ PAS LES VIS.

SPEAKER CAUTION: USE 8 OHM MIN. SPEAKERS.
ATTENTION: UTILIZER DES HAUT-PARLEURS 8 OHM MIN.

SWITCHED UNSWITCHED
POWER FUSE CONTROL

OUTLET RATING:
SPECIFICATION DU RECEPTACLE:
230V, 50/60Hz
SWITCHED: CONTRÔLE: 50W. MAX.
UNSWITCHED: NONCONTRÔLE:
150W. MAX.

ELECTRICAL RATING
SPECIFICATIONS ELECTRIQUES:

A.C. INPUT
115V/ACC. 560W

R. CHANNEL

3.5A F.B.

R G G L

SPEAKER B

R G G L

SPEAKER A

L. CHANNEL

3.5A F.B.

M. A. BHP. A. OUT - AUX - TUNER - 2 PHONO 1
LEFT
RIGHT

OUT-2-IN OUT-1-IN REC./PB
LEFT
RIGHT
TAPE RECORDER

GROUND

OPERATING MANUAL



SCOTT
A437

SCOTT STEREO AMPLIFIER A437

INPUT
LINE
TUNER
AUX



SELECTOR



MODE



—10dB



BASS

TREBLE



0dB — POWER LEVEL — 0dB



FILTER

LOW HIGH



LOAD

IMP 4Ω

IMP

4Ω

TAPE

REVERSE

REVERSE

PHONES

POWER